

Intelligent Designs 2000 Corp. Denver, Colorado 80211 www.GOBIRACKS.com

GOBI HUMMER H3 TIRE CARRIER ROOF RACK SPECIFICATIONS

SPE CIFICATIONS:

WEIGHT88 lbs(39.92kg)LENGTH96"(2.438M)WIDTH47" (1.9M)HEIGHT91/2" (.241M) down to 4 5/8" (.117M) at low pointPAINTBlack textured semi gloss Powder coat with
WIDTH 47" (1.9M) HEIGHT 9 1/2" (.241M) down to 4 5/8" (.117M) at low point
HEIGHT 91/2" (.241M) down to 45/8" (.117M) at low point
DAINT Diada tarthwad asmi si as Downlaw as at with
PAINT Black textured semi gloss Powder coat with Gray epoxy anti-rust undercoat
USABLE CARGO 7.5 sq.ft. (.696m2) SPACE (with sun roof opening)
USABLE CARGO 13 sq.ft. (1.21m2) SPACE (with out sun roof opening)
LOAD LIMIT 300 1bs (11 1.97kg) for safe driving loads. 8001bs. static load 1 excluding spare tire spread over entire roof rack evenly
CARGO DECK 3/4" 9 gauge expanded metal welded in place
FRAME 16 gauge 1.0" (.025 m) welded tubul ar frame
VEHICLE 8 - 3/16" (4.72mm) laser cut formed brackets black ATTACHMENT powder coated Gray epoxy anti-rust undercoat
FRONT LIGHT BAR 4 Place light bar for use with up to 8" diameter off road lights
REAR LIGHT BAR 2 independent rear light tabs for use with up to 3" x 6" lights
TIRE CARRIER. 3 Sided semi-circular tublar steel frame, 6 point tire contact surface with adjustable height wheel hub support, designed to be used with OEM Factory supplied spare tire and lug nuts
FAIRING 44"(1.2M) Black powder coated aluminum wind deflector with 3 mounting brackets attached to front light Bar
HARDWARE Stainless Steel

Height of vehicle with roof rack spare tire installed on rack and OEM factory equipped tires is 7'-8" (2.34M)

GOBI H3 TIRE CARRIER ROOF RACK SPECIFICATIONS	PARI NO. GH3TC	sheet 1 of 1
---	----------------	------------------